



## Webbing Slings r-PET recycled material

### Информация за продукта



Haklift webbing slings r-PET are made from high-strength **recycled** polyester (r-PET) yarn having a robust protective cover. Because it is made from r-PET yarn, this product **has up to 65% CO2 reduction\*** compared to the standard PRS webbing sling.

Because of this sustainability enhancement, this product is approved to be part of Lifting Solution Group's Aspire range™. In November 2023, this product won the prestigious LEEA Sustainable Award.

The PRS r-PET slings are color coded for quick and easy identification of the Working Load Limit (WLL).

- Safe – All r-PET slings are made from high-strength recycled polyester and tested in accordance with EN 1492-1
- Double layer Duplex webbing slings
- Each sling carries a blue label giving the correct WLL for different load connection methods and angles
- Each sling is marked with a unique serial number for safe sling registration
- Serial number is expressed both in a numeric format as well as Barcode for quick registration and maintenance
- Year/Month calendar printed on the label where the next inspection date can be marked or punched
- Printing on the blue label is protected by an additional transparent plastic layer for long life
- All webbing slings carry a white label showing a pictogram with important user warning instructions
- QR code for on-site access to Multilanguage user manuals
- Test certificate and Declaration of Conformity enclosed with each sling

**Chemical resistance:** Resistant to most acids, but not strong alkalizes.

**Stretch at working load:** 2-3%.

**Length tolerance:** Nominal length (EWL)  $\pm 2\%$ .

\*A 3rd party climate LCA with a cradle-to-gate perspective according to ISO14067 has shown that our r-PET webbing slings have up to 65% less CO2e emissions than our standard product. This means that our products are not only better for the environment but also make a positive contribution to reducing CO2 emissions.

Продуктов номер	WLL тон	Работна дължина m	Широчина мм	Цвят	Тегло кг	Delivery time
SNV101RPET	1	1	50	лилав	0,25	10
SNV102RPET	1	2	50	лилав	0,4	10
SNV103RPET	1	3	50	лилав	0,6	10
SNV104RPET	1	4	50	лилав	0,7	10
SNV106RPET	1	6	50	лилав	1,25	10
SNV201RPET	2	1	60	зелен	0,45	10
SNV202RPET	2	2	60	зелен	0,7	10
SNV203RPET	2	3	60	зелен	1,1	10
SNV204RPET	2	4	60	зелен	1,55	10
SNV206RPET	2	6	60	зелен	2,25	10
SNV301RPET	3	1	90	жълт	0,75	10
SNV302RPET	3	2	90	жълт	1,1	10
SNV303RPET	3	3	90	жълт	1,6	10
SNV304RPET	3	4	90	жълт	2,35	10
SNV306RPET	3	6	90	жълт	3	10