

Electric winch TRBoxter BT 1-speed

Информация за продукта



General:

Electric winch for loads from 250 up to 1500 kg with low voltage control and 1 speed.

Multifunctional electric winch offering many rope attachments, rope outlets and options. Robust and compact, it benefits of a high operating factor for all kind of applications such as for example: Industrial applications, Building and public works, Theatre applications, Integration into many types of devices, cranes, material lifts etc.

Technical properties:

- Welded steel drum.
- Aluminium casing.
- The low voltage control protects the user from electrical risks.
- Asynchronous, single phase motors (230 V – 50 Hz P=0.75 or 1.1 kW depending on the models)
- Threephase motors (400 V – 50 Hz P= 0.75 or 1.1 kW depending on the models).
- Reducer sealed in oil bath with helical gears.
- 24 V or 190 V direct current electromagnetic brake (depending on the models).
- Electrical equipment under sealed cover.
- Very low voltage, 24 V remote control with socket – IP 65 protection.

Optional:

- Limit switch
- Radio control
- Load limiter
- Lengthened drum models. Wire rope capacity will increase by 1.5 x standard capacity.

Маркировка: Съгласно релевантния стандарт, CE - маркировка

Стандарт: EN 14492-1

Продуктов номер	WLL	Височина на повдигане	Модел	За въже Ø	Power	WLL от върха	Speed top layer	Мощност	Speed 1st layer	FEM	Number of layers	Тегло	Delivery time
	тон	м		мм		тон	m/min	kW	m/min			кг	

TRBOXTER253BT14	0,29	56	TRBOXTER253BT14	5	3Ph-400V	0,25	15,4	0,75	13,3	1Am	3	49	14
TRBOXTER253BT9	0,29	56	TRBOXTER253BT9	5	3Ph-400V	0,25	9,4	0,75	8,1	1Am	3	49	14
TRBOXTER251BT21	0,29	56	TRBOXTER251BT21	5	1Ph-230V	0,25	23	1,1	19,8	1Am	3	51	14
TRBOXTER253BT21	0,29	56	TRBOXTER253BT21	5	3Ph-400V	0,25	23	1,1	19,8	1Am	3	51	14
TRBOXTER253BT43	0,29	56	TRBOXTER253BT43	5	3Ph-400V	0,25	46,6	2,2	40,3	1Am	3	59	14
TRBOXTER353BT9	0,4	56	TRBOXTER353BT9	5	3Ph-400V	0,35	9,4	0,75	8,1	1Bm	3	49	14
TRBOXTER351BT14	0,4	56	TRBOXTER351BT14	5	1Ph-230V	0,35	15,4	1,1	13,3	1Bm	3	51	14
TRBOXTER353BT14	0,4	56	TRBOXTER353BT14	5	3Ph-400V	0,35	15,4	1,1	13,3	1Bm	3	51	14
TRBOXTER353BT26	0,4	56	TRBOXTER353BT26	5	3Ph-400V	0,35	29,8	2,2	25,7	1Bm	3	59	14
TRBOXTER503BT4	0,6	42	TRBOXTER503BT4	7	3Ph-400V	0,5	4,9	0,75	4	1Bm	3	49	14
TRBOXTER503BT4	0,6	42	TRBOXTER503BT4	7	3Ph-400V	0,5	4,9	0,75	4	1Bm	3	49	14
TRBOXTER501BT11	0,6	42	TRBOXTER501BT11	7	1 Ph - 230 V	0,5	12,2	1,1	10	1Bm	3	51	14
TRBOXTER503BT11	0,6	42	TRBOXTER503BT11	7	3Ph-400V	0,5	12,2	1,1	10	1Bm	3	51	14
TRBOXTER501BT11ST	0,6	42	TRBOXTER501BT11ST	7	1Ph-230V	0,5	12,2	1,1	10	1Bm	3	51	14
TRBOXTER503BT11ST	0,6	42	TRBOXTER503BT11ST	7	3Ph-230/400V	0,5	12,2	1,1	10	1Bm	3	51	14
TRBOXTER503BT21	0,6	42	TRBOXTER503BT21	7	3Ph-400V	0,5	24,2	2,2	20	1Bm	3	59	14
TRBOXTER0603BT05	0,75	93	TRBOXTER0603BT05	7	3Ph-400V	0,6	6	0,75	4,8	1Am	4	88	14
TRBOXTER603BT15	0,75	93	TRBOXTER603BT15	7	3Ph-400V	0,6	18,6	2,2	14,9	1Am	4	100	14
TRBOXTER0603BT10	0,75	93	TRBOXTER0603BT10	7	3Ph-400V	0,6	11	1,5	8,8	1Am	4	101	14
TRBOXTER0603BT20	0,75	93	TRBOXTER0603BT20	7	3Ph-400V	0,6	22,5	3	17,9	1Bm	4	104	14
TRBOXTER0603BT30	0,75	93	TRBOXTER0603BT30	7	3Ph-400V	0,6	31,9	4	25,5	1Bm	4	107	14
TRBOXTER0803BT05	0,95	59	TRBOXTER0803BT05	8	3Ph-400V	0,8	5,2	1,1	4,3	1Bm	3	92	14
TRBOXTER0803BT10	0,95	59	TRBOXTER0803BT10	8	3Ph-400V	0,8	10,3	2,2	8,7	1Bm	3	100	14

TRBOXTER0803BT13	0,95	59	TRBOXTER0803BT13	8	3Ph-400V	0,8	14,3	3	12	1Bm	3	104	14
TRBOXTER0803BT17	0,95	59	TRBOXTER0803BT17	8	3Ph-400V	0,8	17,8	4	15	1Bm	3	107	14
TRBOXTER0993BT13	0,99	14,5	TRBOXTER0993BT13	9	3Ph-400V	0,99	12,1	3	12,1	1Bm	1	104	14
TRBOXTER0993BT17	0,99	14,5	TRBOXTER0993BT17	9	3Ph-400V	0,99	15,1	4	15,1	1Cm	1	108	14
TRBOXTER0993BT10	1,1	34	TRBOXTER0993BT10	9	3Ph-400V	0,99	10,6	2,2	8,7	1Bm	2	100	14
TRBOXTER0993BT05	1,2	53	TRBOXTER0993BT05	9	3Ph-400V	0,99	5,3	1,1	4,4	1Bm	3	92	14
TRBOXTER1503BT04	1,5	11,5	TRBOXTER1503BT04	11,5	3Ph-400V	1,5	4,4	1,5	4,4	1Bm	1	101	14
TRBOXTER1503BT09	1,5	11,5	TRBOXTER1503BT09	11,5	3Ph-400V	1,5	8,8	1	8,8	1Cm	1	104	14

Чертеж

