



# High Speed Hoists Red Rooster TCS-500 / TCS-980

#### **Product information**

Highspeed air chain hoist for loads from 500 up to 980 kg.

RED ROOSTER Air Chain Hoists are especially developed for the "Material Handling Industry". For example: warehousing, packaging etc.

These hoists have a very high lifting and lowering speed, making them very suitable for applications with long lifting heights.

- Very high lifting and lowering speeds
- · Maximum speed adjustable, lifting and lowering speed independent from each other.
- Precise variable speed control (cord and pendant control).
- Optimum control of the load, very precise positioning.
- · Compact and light weight.
- Exhaust hose easy to assemble
- Endstop system
- Air motor is cooled by the exhaust air (internal)
- · Cord control or pendant control
- Low noise level
- · Aluminum housing

#### Optional:

- Marine Specification/Corrosion resistant
- Paint systems from C2 Industrial to C5 Offshore specification (Red finish as standard. Other RAL colours available on request).
- · Choice of pendants.
- Radio control pendant for electro pneumatic controls.
- · Control systems.
- Chain collectors (PVC, galvanised or stainless steel).
- · Various types of hook or clevis available.
- Air supply systems and valves.
- · Air Service unit.
- · Piped away exhaust air.
- · In house design for "specials".
- Festoon systems.
- · Main air shut off valve.

#### ATEX:

• According to EC Directive 94/9/EC (Ex Classification)

### Recommended:

We strongly recommend using an air handling unit, e.g. from SMC (offered separately).

Features: Very high lifting and lowering speeds.

Part code			Number of falls	consumption	Air consumption lowering (I/sec)	speed with	Lowering speed with max.load m/min		Workingpressure n bar		Min. Hosediam	Load A B C n. chain mmmmm mm				X Z V mmmm		Delivery time days
16.30TCS- 500C	TCS- 500C	0.5	1	28	33	17	34	1/2"BSPT	6	33	1/2"	6.3x19.1415 255 1	3 68 205 163 1	.5 35 2	<u>?</u> 2 22	40 210	19	21
16.30TCS- 500PE		0.5	1	28	33	17	34	1/2"BSPT	6	33	1/2"	6.3x19.1415 255 1	3 68 205 163 1	.5 35 2	22 22	40 210	19	21
16.30TCS- 980C2		0.98	2	28	33	8.5	17	1/2"BSPT	6	17	1/2"	6.3x19.1510 205 12	23 37 163 205 3	0 40 2	<u>1</u> 9 25	40 225	24	21
16.30TCS- 980P2E		0.98	2	28	33	8.5	17	1/2"BSPT	6	17	1/2"	6.3x19.1510 205 12	23 37 163 205 3	0 40 2	29 25	40 225	24	21

Technical data / Spare Parts

## Blueprint

