



Electric Chain Hoist LIFTKET STAR 125 – 6.300 kg

Product information

The LIFTKET product portfolio offers you standardized hoists that can be adjusted to your requirements in a modular way, as well as highly specialized solutions. Larger lifting and operating heights are just as viable as deviating voltages and special solutions of any kind.

Features:

- Power supply 400 V, 3 phase, 50 Hz
- From 125 kg to 6.300 kg we lift everything that moves you
- FEM ratings from Fem 1Bm to 4m (ISO M3 to M7)
- Protection class IP55, insulation class F
- Galvanized load chain to DIN 818-7 quality class DAT
- A wide range of options can be selected as standard
- Optional one or two lifting speeds from 2 to 32 m/min.
- With heavy-duty end position switch-off as standard (at 24VAC)
- Up to 200 meters high safely and anywhere
- Patented safety-brake-clutch system
- Modular hoist design
- Simply and cost effective maintenance and repair
- A unique ID makes it possible to trace exactly when a particular electric chain hoist was built by whom and with which materials – even after 10 years

Trolleys/Boogies: Manual or electric trolleys in various designs for each steel section girder.

Marking: CE-marked

Note: Standard version delivered with lifting eye (connection between crane and trolley). Alternatively, comes with suspension hook. Standard stock hoist with 6 m lifting height.

Part code	Code	WLL	Lifting height	Lifting speed	Number of falls	Motor	Duty rating	% ED	Class ISO/FEM	Lifting speed at 50 Hz	Load chain	A mm	B mm	C mm	G	G2	øN	J	Weight	Delivery time
		ton	m	m/min		kW				m/min	mm								kg	days
5401	031/530	125	6	8/2	1	0.32/0.08	60/40		M7 / 4m	8/2	5.2x15	212	192	220	380	406	25	20	18	35
5401	031/51	0.25	6	8/2	1	0.32/0.08	50/25		M6 / 3m	8/2	5.2x15	212	192	220	380	406	25	20	18	35
5401	031/51	0.5	3	4/1	2	0.32/0.08	50/25		M6 / 3m	4/1	5.2x15	212	192	220	380	415	35	20	21	1
5401	071/54	0.5	6	8/2	1	0.9/0.2	60/25		M5 / 2m	8/2	7.2x21	266	232	274	388	436	35	20	42	1
5401	071/55	1	6	6/1.5	1	1.1/0.2	60/25		M5 / 2m	6/1.5	7.2x21	266	232	274	413	460	35	22	42	1
SKT2000KV2	071/55	2	6	3/0.75	2	1.1/0.2	60/25		M5 / 2m	3/0.75	7.2x21	266	232	274	514	561	35	28	47	1
SKT3200KV2	091/55	3.2	3	4/1	2	3.0/0.75	60/25		M5 / 2m	4/1	9x27	359	283	359	620	655	40	30	97	1
SKT5000KV2	111/52	5	3	5/1.25	2	4.4/1.1	40/25		M5 / 2m	5/1.25	11.3x31	359	291	367	740	807	50	42	130	35

Technical data

Blueprint

