

## Tiger winches



### Product information

High quality Tiger winch is suitable for both lifting and pulling.

The winch is equipped with an automatic brake function which ensures that there is no risk of load falling or sliding. Brake system and components are encased and protected from dust and rain.

Straps and wire ropes are also available separately as spare parts.

Steel wire rope or strap need to order separately.

Product equipped with wire rope can be used for lifting and pulling and product with strap only for pulling. Check the ropes and traps from technical data tab.

All the dimension data can be found on the documents tab

**Material:** Steel

**Marking:** According to standard

**Temperature range:** -40°C - (+)80°C

**Finish:** High quality powder coat, yellow

**Standard:** EN 13157

Part Code	WLL ton	Gear ratio	Length handle mm	Wire capacity mtr	Drum diameter mm	Pulling capacity t	Webbing length m	Weight kg	Delivery time
VINTT360	0.185	4,1:1	160	36	40	0.37	9.1	3	0
VINTT550	0.275	4,1:1	210	23	50	0.55	8.5	3.5	0
VINTT800	0.41	5:01	320	24	70	0.82	14.1	8	0
VINTT1180	0.6	10:01	320	18	82	1.2	10.6	10.5	0

## Technical data

### WIRE ROPES WITH LATCH HOOK (for lifting and pulling)

For winch t	Length m	Diameter mm	Breaking strength kg
0,185 / 0,37	30	4	1270
0,275 / 0,55	20	5	2000
0,41 / 0,82	22	6	3000
0,6 / 1,2	16	8	4500

### STRAPS WITH LATCH HOOK (only for pulling)

For winch t	Length m	Diameter mm	Breaking strength kg
0,185 / 0,37	6	48	2068
0,275 / 0,55	6	48	2068
0,41 / 0,82	9	54	2864
0,6 / 1,2	9	60	4136