



# Aluminium body wire rope hoists

#### **Product information**

High quality aluminium wire rope hoist for pulling and lifting. The hoist does not have a wire drum as the wire goes through the hoist. Lifting and pulling speed is app. 3 m/min. The hoist is equipped with 20 m wire rope with a safety hook as a standard.

Features: 800/1600/3200 kg models equipped with a carrying handle Material: Aluminum Marking: According to standard, CE-marked Finish: Painted, blue Standard: EN 13157 Note: Other wire rope lengths are also available upon request.

Safety factor: 5:1


Part code	WLL ton	Rope Ø mm	Rope length m	Lever length mm	Pulling capacity t	Weight kg	Delivery time days
LOABT800	0.8	8.3	20	800	1.2	6.6	1
LOABT1600	1.6	11	20	1,200	2.4	12.5	1
LOABT3200	3.2	16	20	1,200	4	23.4	1
LOABT5400	5.4	20	20	1,120	8	61	1

### WEIGHTS

Product code	Hoist kg	20 m wire rope kg	Total kg
LOABT800	6,6	7,2	13,8
LOABT1600	12,5	12,1	24,6
LOABT3200	23,4	22,8	46,2
LOABT5400	61	37,5	98,5

## WIDTH OF ANCHOR POINT

Product code	Width mm
LOABT800	30
LOABT1600	40
LOABT3200	52
LOABT5400	63



#### SPARE PARTS

Spare part (product

couc,

LO80VAI20	Replacement wire rope 0,8 t   20 m with latch hook	LOABT800
LO16VAI20	Replacement wire rope 1,6 t   20 m with latch hook	LOABT1600
LO32VAI20	Replacement wire rope 3,2 t   20 m with latch hook	LOABT3200
LO08SOKKA	Action (forward) lever's overload protection/shearing pin	LOABT800
LO16SOKKA	Action (forward) lever's overload protection/shearing pin	LOABT1600
LO32SOKKA	Action (forward) lever's overload protection/shearing pin	LOABT3200
LO54SOKKA	Action (forward) lever's overload protection/shearing pin	LOABT5400
LOABT800VAR	Operating hand lever	LOABT800
LOABT1600VAR	Operating hand lever	LOABT1600
LOABT3200VAR	Operating hand lever	LOABT3200

Also other wire rope lengths and spare parts available with a delivery time, ask our sales for more information