



## Push trolley

### Product information

Push trolley for IPE and T beams. The wheels are equipped with duration lubricated ball bearings. The hoist or lifter can be attached directly to the trolley eye with a hook or a shackle.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -10°C - (+)50°C

**Finish:** Painted, yellow

**Standard:** EN 13157

**Safety factor:** 4:1

| Part code | WLL ton | Beam width mm | Minimum radius mm | B mm | D mm | E mm | F mm | G mm | H mm | J mm | K mm  | L mm | Weight kg | Delivery time days |
|-----------|---------|---------------|-------------------|------|------|------|------|------|------|------|-------|------|-----------|--------------------|
| SIVA05H   | 0.5     | 55-220        | 500               | 285  | 3    | 40   | 12.5 | 25   | 80   | 198  | 158   | 55   | 5         | 1                  |
| SIVA05HL  | 0.5     | 55-305        | 500               | 385  | 3    | 40   | 12.5 | 25   | 80   | 198  | 158   | 55   | 5.4       | 1                  |
| SIVA10H   | 1       | 58-220        | 700               | 300  | 3    | 31   | 17   | 29   | 96   | 238  | 183   | 68   | 8.8       | 1                  |
| SIVA10HL  | 1       | 58-305        | 700               | 238  | 3    | 31   | 17   | 29   | 96   | -    | 183   | 68   | 9.3       | 1                  |
| SIVA20H   | 2       | 66-220        | 900               | 300  | 3    | 31   | 20   | 36   | 110  | 277  | 208   | 80   | 14        | 1                  |
| SIVA20HL  | 2       | 66-305        | 900               | 405  | 3    | 31   | 20   | 36   | 110  | 277  | 208   | 80   | 14.8      | 1                  |
| SIVA30H   | 3       | 74-220        | 1,200             | 328  | 3    | 31   | 26   | 46   | 132  | 324  | 249   | 100  | 23        | 1                  |
| SIVA30HL  | 3       | 74-305        | 1,200             | 429  | ~3   | 31   | 26   | 46   | 132  | 324  | 249   | 100  | 24.1      | 1                  |
| SIVA50H   | 5       | 90-220        | 1,000             | 354  | 5    | 40   | 28   | 52   | 155  | 373  | 296.5 | 120  | 40        | 1                  |
| SIVA50HL  | 5       | 90-305        | 1,000             | 435  | ~5   | 40   | 28   | 52   | 155  | 373  | 296.5 | 120  | 41.1      | 1                  |

## Technical data / Spare Parts

### AXEL OF THE TROLLEY

| Product code | Thread | Thread pitch mm |
|--------------|--------|-----------------|
| SIVA05H      | M24    | 1,5             |
| SIVA10H      | M30    | 1,5             |
| SIVA20H      | M36    | 1,5             |
| SIVA30H      | M42    | 2               |
| SIVA50H      | M48    | 2               |

**Note!** One end is left-hand thread and the other end is right hand thread

Blueprint

