



Alloy Swivel Bearing Hoist Hook 8-175N

Product information

Built with ball bearing and enables full swivel feature under load. At least 25% greater WLL than traditional Grade 8 products. Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL. Magnaflux crack detection is performed 100% on each batch.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard

Temperature range: Tempering temperature minimum 400°C

Standard: EN 1677-1

Safety factor: 4:1

Grade: 10

Part Code	Chain diameter mm	WLL ton	Hook (*) code (*)	A mm	B mm	C mm	D mm	G mm	H mm	K mm	L mm	P mm	P1 mm	T mm	Weight kg
SALKAL1006KL	6	1.5	BB	32	23	25	12	80	21	126	158	24	19	18	0.7
SALKAL1078KL	7-8	2	CC	36	29	26	13	91	25	143	181	24	20	22	0.9
SALKAL1010KL	10	3	DD	41	35	29	16	102	29	172	217	28	25	24	1.6
SALKAL1013KL	13	5	EE	46	44	38	21	130	36	211	269	35	31	31	3.2
SALKAL1016KL	16	7	FF	61	51	49	23	166	46	258	328	43	39	42	5.7
SALKAL1020KL	20	11	GG	74	82	62	25	196	58	326	409	61	57	48	9.5
SALKAL1022KL	22	15	HH	97	96	65	33	221	64	372	471	72	62	56	16

Blueprint

