



## Chain sling 1-leg with latch hook and grab hook, grade 80

### Product information

1-Leg chain sling assembly equipped with latch hook and grab hook. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hook.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, black / yellow

**Standard:** EN 818-4

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

Part code	Chain diameter mm	WLL ton	Choke Hitch ton	Delivery time days
NKS06101L	6	1.12	0.896	1
NKS07101L	7	1.5	1.2	1
NKS08101L	8	2	1.6	1
NKS10101L	10	3.15	2.52	1
NKS13101L	13	5.3	4.24	1
NKS16101L	16	8	6.4	1
NKS20101L	20	12.5	10	1
NKS22101L	22	15	12	1
NKS26101L	26	21.2	16.96	1
NKS32101L	32	31.5	25.2	1

## Blueprint

