

Chain sling 1-leg with safety hook and grab hook, grade 80

Product information



1-Leg chain sling assembly equipped with safety hook and grab hook. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hook.

... [Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, black / yellow

Standard: EN 818-4

Warning: Not to be heat-treated


Safety factor: 4:1

Grade: 8

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

Chain sling 1-leg with safety hook and grab hook, grade 80

Blueprint



Technical data / Spare Parts

Part code	Chain diameter mm	WLL ton	Choke Hitch ton
NKV06101L	6	1.12	0.896
NKV07101L	7	1.5	1.2
NKV08101L	8	2	1.6
NKV10101L	10	3.15	2.52
NKV13101L	13	5.3	4.24
NKV16101L	16	8	6.4
NKV20101L	20	12.5	10
NKV22101L	22	15	12
NKV26101L	26	21.2	16.96
NKV32101L	32	31.5	25.2