



Chain sling 2-legs with latch hooks and grab hooks, grade 80

Product information

2-legs chain sling assembly equipped with latch hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, black / yellow

Standard: EN 818-4

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

Part code	Chain diameter mm	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	Delivery time days
NKS06201L	6	1.6	1.12	1
NKS07201L	7	2.12	1.5	1
NKS08201L	8	2.8	2	1
NKS10201L	10	4.25	3.15	1
NKS13201L	13	7.5	5.3	1
NKS16201L	16	11.2	8	1
NKS20201L	20	17	12.5	1
NKS22201L	22	21.2	15	1
NKS26201L	26	30	21.2	1
NKS32201L	32	45	31.5	1

Blueprint

