



Chain sling 2-legs with safety hooks and grab hooks, grade 100

Product information

2-legs chain sling assembly equipped with safety hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

Material: Steel

Marking: CE-marked

Temperature range: -29 - (+)205°C

Finish: Painted, blue

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

| Part code | Chain diameter mm | WLL 0-45° t | WLL 45-60° t | Delivery time days |
|------------|----------------------|----------------|-----------------|-----------------------|
| NKVE06201L | 6 | 1.96 | 1.4 | 1 |
| NKVE08201L | 8 | 3.5 | 2.5 | 1 |
| NKVE10201L | 10 | 5.6 | 4 | 1 |
| NKVE13201L | 13 | 9.5 | 6.7 | 1 |
| NKVE16201L | 16 | 14 | 10 | 1 |
| NKVE20201L | 20 | 22.4 | 16 | 1 |
| NKVE22201L | 22 | 26.6 | 19 | 1 |

Blueprint

