

## Chain sling 2-legs with safety hooks and grab hooks, grade 80

### Product information



2-legs chain sling assembly equipped with safety hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

[... Read more](#)

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, black / yellow

**Standard:** EN 818-4

**Warning:** Not to be heat-treated


**Safety factor:** 4:1

**Grade:** 8

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

## Chain sling 2-legs with safety hooks and grab hooks, grade 80

### Blueprint



### Technical data / Spare Parts

| Part code | Chain diameter<br>mm | WLL 0-45°<br>t | WLL 45-60°<br>t |
|-----------|----------------------|----------------|-----------------|
| NKV06201L | 6                    | 1.6            | 1.12            |
| NKV07201L | 7                    | 2.12           | 1.5             |
| NKV08201L | 8                    | 2.8            | 2               |
| NKV10201L | 10                   | 4.25           | 3.15            |
| NKV13201L | 13                   | 7.5            | 5.3             |
| NKV16201L | 16                   | 11.2           | 8               |
| NKV20201L | 20                   | 17             | 12.5            |
| NKV22201L | 22                   | 21.2           | 15              |
| NKV26201L | 26                   | 30             | 21.2            |
| NKV32201L | 32                   | 45             | 31.5            |