

## Chain sling 2-legs with safety hooks, grade 80

### Product information



2-legs chain sling assembly equipped with safety hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

... [Read more](#)

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, black / yellow

**Standard:** EN 818-4

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

## Chain sling 2-legs with safety hooks, grade 80

### Blueprint



### Technical data / Spare Parts

Part code	Chain diameter mm	WLL 0-45° t	WLL 45-60° t
NKV06201	6	1.6	1.12
NKV07201	7	2.12	1.5
NKV08201	8	2.8	2
NKV10201	10	4.25	3.15
NKV13201	13	7.5	5.3
NKV16201	16	11.2	8
NKV20201	20	17	12.5
NKV22201	22	21.2	15
NKV26201	26	30	21.2
NKV32201	32	45	31.5