



Chain sling 3-legs with latch hooks and grab hooks, grade 100

Product information

3-legs chain sling assembly equipped with latch hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

Material: Steel

Marking: CE-marked

Temperature range: -29 - (+)205°C

Finish: Painted, blue

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

| Part code | Chain diameter mm | WLL 0-45° t | WLL 45-60° t | Delivery time days |
|------------|----------------------|----------------|-----------------|-----------------------|
| NKSE06301L | 6 | 2.94 | 2.1 | 1 |
| NKSE08301L | 8 | 5.25 | 3.75 | 1 |
| NKSE10301L | 10 | 8 | 5.7 | 1 |
| NKSE13301L | 13 | 14 | 10 | 1 |
| NKSE16301L | 16 | 21 | 15 | 1 |
| NKSE20301L | 20 | 33.6 | 24 | 1 |
| NKSE22301L | 22 | 39.9 | 28.5 | 1 |

Blueprint

