

Chain sling 3-legs with safety hooks and grab hooks, grade 80

Product information



3-legs chain sling assembly equipped with safety hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

... [Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, black / yellow

Standard: EN 818-4

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

Chain sling 3-legs with safety hooks and grab hooks, grade 80

Blueprint



Technical data / Spare Parts

Part code	Chain diameter mm	WLL 0-45° t	WLL 45-60° t
NKV06301L	6	2.36	1.7
NKV07301L	7	3.15	2.24
NKV08301L	8	4.25	3
NKV10301L	10	6.7	4.75
NKV13301L	13	11.2	8
NKV16301L	16	17	11.8
NKV20301L	20	26.5	19
NKV22301L	22	31.5	22.4
NKV26301L	26	45	31.5
NKV32301L	32	67	47.5