



Chain sling 3-legs with safety hooks and grab hooks, grade 80

Product information

3-legs chain sling assembly equipped with safety hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, black / yellow

Standard: EN 818-4

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

The last two numbers of the product code refer to the length (L-length): 01 = 1.0 m.

| Part Code | Chain size mm | WLL 45- 60° ton | WLL 0-45° ton |
|-----------|------------------|--------------------|------------------|
| NKV06301L | 6 | 1.7 | 2.36 |
| NKV07301L | 7 | 2.24 | 3.15 |
| NKV08301L | 8 | 3 | 4.25 |
| NKV10301L | 10 | 4.75 | 6.7 |
| NKV13301L | 13 | 8 | 11.2 |
| NKV16301L | 16 | 11.8 | 17 |
| NKV20301L | 20 | 19 | 26.5 |
| NKV22301L | 22 | 22.4 | 31.5 |
| NKV26301L | 26 | 31.5 | 45 |
| NKV32301L | 32 | 47.5 | 67 |

Blueprint

