



Chain sling 4-legs with latch hooks and grab hooks, grade 80

Product information

4-legs chain sling assembly equipped with latch hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, black / yellow

Standard: EN 818-4

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

Part Code	Chain size mm	WLL 45- 60° ton	WLL 0-45° ton	Delivery time
NKS06401L	6	1.7	2.36	-
NKS07401L	7	2.24	3.15	-
NKS08401L	8	3	4.25	-
NKS10401L	10	4.75	6.7	-
NKS13401L	13	8	11.2	0
NKS16401L	16	11.8	17	-
NKS20401L	20	19	26.5	-
NKS22401L	22	22.4	31.5	-
NKS26401L	26	31.5	45	-
NKS32401L	32	47.5	67	-

Blueprint

