



Chain sling 4-legs with latch hooks and grab hooks, grade 80

Product information

4-legs chain sling assembly equipped with latch hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, black / yellow

Standard: EN 818-4

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

Part code	Chain diameter mm	WLL 0-45° t	WLL 45-60° t	Delivery time days
NKS06401L	6	2.36	1.7	1
NKS07401L	7	3.15	2.24	1
NKS08401L	8	4.25	3	1
NKS10401L	10	6.7	4.75	1
NKS13401L	13	11.2	8	1
NKS16401L	16	17	11.8	1
NKS20401L	20	26.5	19	1
NKS22401L	22	31.5	22.4	1
NKS26401L	26	45	31.5	1
NKS32401L	32	67	47.5	1

Blueprint

