Chain sling 4-legs with latch hooks, grade 80

Product information



4-legs chain sling assembly equipped with safety hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

... *Read more*

Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, black / yellow
Standard: EN 818-4
Warning: Not to be heat-treated

Safety factor: 4:1
Grade: 8

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Chain sling 4-legs with latch hooks, grade 80

Blueprint



Technical data / Spare Parts

Part code	Chain diameter mm	WLL 0-45° t	WLL 45-60° t
NKS06401	6	2.36	1.7
NKS07401	7	3.15	2.24
NKS08401	8	4.25	3
NKS10401	10	6.7	4.75
NKS13401	13	11.2	8
NKS16401	16	17	11.8
NKS20401	20	26.5	19
NKS22401	22	31.5	22.4
NKS26401	26	45	31.5
NKS32401	32	67	47.5

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved