

## Chain sling 4-legs with latch hooks, grade 80

### Product information



4-legs chain sling assembly equipped with safety hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

... [Read more](#)

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, black / yellow

**Standard:** EN 818-4

**Warning:** Not to be heat-treated


**Safety factor:** 4:1

**Grade:** 8

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

## Chain sling 4-legs with latch hooks, grade 80

Blueprint



Technical data / Spare  
Parts

| Part code | Chain diameter<br>mm | WLL 0-45°<br>t | WLL 45-60°<br>t |
|-----------|----------------------|----------------|-----------------|
| NKS06401  | 6                    | 2.36           | 1.7             |
| NKS07401  | 7                    | 3.15           | 2.24            |
| NKS08401  | 8                    | 4.25           | 3               |
| NKS10401  | 10                   | 6.7            | 4.75            |
| NKS13401  | 13                   | 11.2           | 8               |
| NKS16401  | 16                   | 17             | 11.8            |
| NKS20401  | 20                   | 26.5           | 19              |
| NKS22401  | 22                   | 31.5           | 22.4            |
| NKS26401  | 26                   | 45             | 31.5            |
| NKS32401  | 32                   | 67             | 47.5            |