



## Chain sling 4-legs with safety hooks and grab hooks, grade 100

### Product information

4-legs chain sling assembly equipped with safety hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

**Material:** Steel

**Marking:** CE-marked

**Temperature range:** -29 - (+)205°C

**Finish:** Painted, blue

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 10

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

| Part Code  | Chain size<br>mm | WLL 45- 60°<br>ton | WLL 0-45°<br>ton | Delivery time |
|------------|------------------|--------------------|------------------|---------------|
| NKVE06401L | 6                | 2.1                | 2.94             | 0             |
| NKVE08401L | 8                | 3.75               | 5.25             | -             |
| NKVE10401L | 10               | 5.7                | 8                | -             |
| NKVE13401L | 13               | 10                 | 14               | -             |
| NKVE16401L | 16               | 15                 | 21               | -             |
| NKVE20401L | 20               | 24                 | 33.6             | -             |
| NKVE22401L | 22               | 28.5               | 39.9             | -             |

Blueprint

