



Chain sling 4-legs with safety hooks and grab hooks, grade 80

Product information

4-legs chain sling assembly equipped with safety hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, black / yellow

Standard: EN 818-4

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

| Part code | Chain diameter mm | WLL 0-45° t | WLL 45-60° t | Delivery time days |
|-----------|----------------------|----------------|-----------------|-----------------------|
| NKV06401L | 6 | 2.36 | 1.7 | 1 |
| NKV07401L | 7 | 3.15 | 2.24 | 1 |
| NKV08401L | 8 | 4.25 | 3 | 1 |
| NKV10401L | 10 | 6.7 | 4.75 | 1 |
| NKV13401L | 13 | 11.2 | 8 | 1 |
| NKV16401L | 16 | 17 | 11.8 | 1 |
| NKV20401L | 20 | 26.5 | 19 | 1 |
| NKV22401L | 22 | 31.5 | 22.4 | 1 |
| NKV26401L | 26 | 45 | 31.5 | 1 |
| NKV32401L | 32 | 67 | 47.5 | 1 |

Blueprint

