



## Chain sling 4-legs with safety hooks, grade 80

## **Product information**

4-legs chain sling assembly equipped with safety hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, black / yellow

Standard: EN 818-4

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

| Part Code | Chain size<br>mm | WLL 45- 60°<br>ton | WLL 0-45°<br>ton |
|-----------|------------------|--------------------|------------------|
| NKV06401  | 6                | 1.7                | 2.36             |
| NKV07401  | 7                | 2.24               | 3.15             |
| NKV08401  | 8                | 3                  | 4.25             |
| NKV10401  | 10               | 4.75               | 6.7              |
| NKV13401  | 13               | 8                  | 11.2             |
| NKV16401  | 16               | 11.8               | 17               |
| NKV20401  | 20               | 19                 | 26.5             |
| NKV22401  | 22               | 22.4               | 31.5             |
| NKV26401  | 26               | 31.5               | 45               |
| NKV32401  | 32               | 47.5               | 67               |

## Blueprint

