Choker chain sling 2-legs with grab hooks, grade 80

Product information

Used for tightening loop lift. Perfect for lifting, among others, pipe bundles, lumber bundles and reinforcement steel. The assemblies include a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the omega connector.

... *Read more*

Material: Steel
Marking: According to standard, CE-marked
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, black / yellow
Standard: EN 818-4
Warning: Not to be heat-treated

Safety factor: 4:1
Grade: 8

The last two numbers of the product code refer to the length (L-length): 01 = 1,0 m.

Haklift Oy
sales@haklift.com
+358 2 511 5511

© October 2026 - All Rights Reserved

Choker chain sling 2-legs with grab hooks, grade 80

Blueprint



Technical data / Spare Parts

Part code	Chain diameter mm	WLL 0-45° t	WLL 45-60° t
NKLI07201L	7	1.7	1.2
NKLI08201L	8	2.2	1.6
NKLI10201L	10	3.5	2.5
NKLI13201L	13	6	4.2
NKLI16201L	16	8.9	6.3

Haklift Oy
sales@haklift.com
+358 2 511 5511

© October 2026 - All Rights Reserved