# Clevis grab hook, grade 80

## Product information



Clevis grab hook is used for shortening chain legs of a sling. The grab hook is attached to the master link with the clevis attachment.

... *Read more*

**Material:** Steel
**Marking:** According to standard, CE-marked
**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%
**Finish:** Painted, yellow
**Standard:** EN 1677-1
**Warning:** Not to be heat-treated


**Safety factor:** 4:1
**Grade:** 8

**Haklift Oy**
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

# Clevis grab hook, grade 80

## Blueprint




## Technical data / Spare Parts

| Part code | Chain diameter mm | WLL ton | A mm | K mm | P mm | F mm | H mm | Weight kg |
|---|---|---|---|---|---|---|---|---|
| LYKH78 | 8 | 2 | 9 | 70 | 11 | 33 | 18 | 0.32 |
| LYKH10 | 10 | 3.15 | 12 | 97 | 13 | 46 | 29 | 0.73 |
| LYKH13 | 13 | 5.3 | 15 | 121 | 16 | 57 | 42 | 1.6 |
| LYKH20 | 20 | 12.5 | 23 | 163 | 24 | 74 | 56 | 5 |

**Haklift Oy**
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved