Eye grab hook, grade 80

Product information



Eye grab hook is used for shortening chain legs of a sling. The grab hook is attached to the master link with the same connection link as the chain.

... *Read more*

Material: Steel
Marking: According to standard, CE-marked
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, yellow
Standard: EN 1677-1
Warning: Not to be heat-treated


Safety factor: 4:1
Grade: 8

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Eye grab hook, grade 80

Blueprint



Technical data / Spare Parts

Part code	WLL ton	For chain Ø mm	A mm	K mm	P mm	Weight kg
LYK6	1.12	6	13,5	49	8	0.14
LYK78	2	7-8	17	59,5	11	0.245
LYK10	3.15	10	20	77,5	13	0.65
LYK13	5.3	13	26	97,5	16,5	1.39
LYK16	8	16	30	106	19	2.2
LYK20	12.5	20	37	140	24	4.6
LYK22	15	22	44	162	28	8.2
LYK26	21.2	26	49	193,5	30	9.8
LYK32	31.5	32	57	227	38	19.4

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved