Foundry eye hook, grade 80

Product information

Foundry eye hook with a wide mouth opening are attached to the chain with connecting slings.

... *Read more*

Material: Steel
Marking: According to standard, CE-marked
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, yellow
Standard: EN 1677-1
Warning: Not to be heat-treated

Safety factor: 4:1
Grade: 8

Haklift Oy
sales@haklift.com
+358 2 511 5511

© October 2026 - All Rights Reserved

Foundry eye hook, grade 80

Blueprint



Technical data / Spare Parts

Part code	WLL ton	For chain Ø mm	P mm	H mm	K mm	D mm	A mm	M mm	Weight kg
VAL6	1.12	6	62	29	163	17	39	26	1
VAL78	2	7/8	63	31	163	18	39	25	1.09
VAL10	3.15	10	76	38	200	22	50	32	2.04
VAL13	5.3	13	89	44	238	27	63	38	3.22
VAL16	8	16	102	52	278	32	76	46	5.53
VAL20	12.5	20	114	65	325	38	89	55	8.75
VAL22	15	22	127	69	361	45	102	57	11.93
VAL26	21.2	26	140	77	402	67	126	66	16.8
VAL32	31.5	32	153	97	461	81	151	80	26.6

Haklift Oy
sales@haklift.com
+358 2 511 5511

© October 2026 - All Rights Reserved