Latch hook with ball bearing swivel, grade 80

Product information



Hook is equipped with spring loaded safety latch. Due to the swivel the hook is easy to align into the wanted direction.

... *Read more*

Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, yellow
Standard: EN 1677-2
Warning: Not to be heat-treated


Safety factor: 4:1
Grade: 8

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Latch hook with ball bearing swivel, grade 80

Blueprint



Technical data / Spare Parts

Part code	WLL ton	For chain Ø mm	A mm	B mm	E mm	K mm	H mm	Weight kg
SALKL78KL	2	8	44,5	41	25	152,5	26	0.95
SALKL10KL	3.15	10	44,5	41	25	161	30	1.71
SALKL13KL	5.3	13	50,5	43,5	35	188,5	37	3.13
SALKL16KL	8	16	63,5	58,5	43	243	46,5	5.44
SALKL20KL	12.5	20	70	67	53	286	56,5	9.5

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved