

## Lifting chain, grade 80

### Product information

Short link lifting chain grade 80 is manufactured according to EN 818-2 standard.

**Material:** Steel

**Marking:** According to standard

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, black

**Standard:** EN 818-2

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8



| Part code | Chain diameter<br>mm | WLL<br>ton | A,  | B, | D, | Weight<br>kg/m | Delivery time<br>days |
|-----------|----------------------|------------|-----|----|----|----------------|-----------------------|
| NK6       | 6                    | 1.12       | 18  | 9  | 6  | 0.8            | 1                     |
| NK7       | 7                    | 1.5        | 22  | 10 | 7  | 1.1            | 1                     |
| NK8       | 8                    | 2          | 24  | 12 | 8  | 1.35           | 1                     |
| NK10      | 10                   | 3.15       | 30  | 14 | 10 | 2.15           | 1                     |
| NK13      | 13                   | 5.3        | 39  | 19 | 13 | 3.5            | 1                     |
| NK16      | 16                   | 8          | 48  | 23 | 16 | 5.5            | 1                     |
| NK20      | 20                   | 12.5       | 60  | 25 | 20 | 8.4            | 1                     |
| NK22      | 22                   | 15         | 66  | 28 | 22 | 10.35          | 1                     |
| NK26      | 26                   | 21.2       | 78  | 35 | 26 | 15.8           | 1                     |
| NK32      | 32                   | 31.5       | 96  | 43 | 32 | 23             | 1                     |
| NK36      | 36                   | 40         | 108 | 49 | 36 | 29             | 14                    |
| NK40      | 40                   | 50         | 120 | 54 | 40 | 36             | 14                    |

## Blueprint

