



Lifting swivel with ball bearing, grade 80

Product information

Lubricated easily rotating swivels for use with lifting chains. Rotates easily also with full load. Equipped with large eye / eye ends.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow/white

Standard: EN 1677-1

Note: Two models

Warning: Not to be heat-treated

Safety factor: 4:1

| Part code | WLL ton | For chain Ø mm | b mm mm | c1 mm | c2 mm | dmm mm | tmm mm | Weight kg | Delivery time days |
|-----------|---------|----------------|---------|-------|-------|--------|--------|-----------|--------------------|
| LEIK6SS | 1.12 | 6 | 32 | 33 | 33 | 12 | 126 | 0.61 | 14 |
| LEIK78SS | 2 | 7/8 | 37 | 40 | 40 | 14 | 153 | 1.07 | 1 |
| LEIK10SS | 3.2 | 10 | 39 | 35 | 65 | 19 | 168 | 1.5 | 1 |
| LEIK13SS | 5 | 13 | 61 | 65 | 100 | 28 | 258 | 3.4 | 1 |
| LEIK16SS | 8.2 | 16 | 73 | 67 | 67 | 17 | 281 | 6.44 | 14 |
| LEIK18SS | 12.8 | 18-20 | 82 | 88 | 88 | 25 | 328 | 7.75 | 14 |

Blueprint

