Lifting swivel with ball bearing, grade 80

Product information



Lubricated easily rotating swivels for use with lifting chains. Rotates easily also with full load. Equipped with large eye / eye ends.

... *Read more*

Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, yellow/white
Standard: EN 1677-1
Note: Two models
Warning: Not to be heat-treated


Safety factor: 4:1

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Lifting swivel with ball bearing, grade 80

Blueprint



Technical data / Spare Parts

Part code	WLL ton	For chain Ø mm	b mm	c1 mm	c2 mm	d mm	t mm	Weight kg
LEIK6SS	1.12	6	32	33	33	12	126	0.61
LEIK78SS	2	7/8	37	40	40	14	153	1.07
LEIK10SS	3.2	10	39	35	65	19	168	1.5
LEIK13SS	5	13	61	65	100	28	258	3.4
LEIK16SS	8.2	16	73	67	67	17	281	6.44
LEIK18SS	12.8	18-20	82	88	88	25	328	7.75

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved