Master link oversized, grade 80

Product information

Extra large masterlink for chain sling assemblies.

... *Read more*

Material: Steel
Marking: According to standard, CE-marked
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, yellow
Standard: EN 1677-4
Warning: Not to be heat-treated

Safety factor: 4:1
Grade: 8

Haklift Oy
sales@haklift.com
+358 2 511 5511

© September 2026 - All Rights Reserved

Master link oversized, grade 80

Blueprint



Technical data / Spare Parts

Part code	WLL ton	For chain, 1-leg mm	For chain, 2-leg mm	A mm	B mm	D mm	Weight kg
NOR16B7	3.2	10	7/8	190	100	16	0.86
NORY025	6.4	13	-	300	210	25	5.53
NOR22B7	7	13	10	210	110	22	1.83
NORY032	11	16	13	300	210	32	5.94
NOR28B7	11.5	16	13/16	270	140	28	3.8
NOR32B6	17	22	20	270	140	32	5.05
NOR38B7	19	22	20	420	220	38	10.78
NOR45B7	27	26	22	470	250	45	17.06
NOR38B6	28	26	22	270	140	38	7.29
NOR50B6	45	36	32	380	200	50	17.65
NOR60B6	65	36	32	430	220	60	28.85

Haklift Oy
sales@haklift.com
+358 2 511 5511

© September 2026 - All Rights Reserved