

## Master link, grade 80

---

### Product information



Masterlink for chain sling assemblies.

[... Read more](#)

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, yellow

**Standard:** EN 1677-4


**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

## Master link, grade 80

### Blueprint



### Technical data / Spare Parts

Part code	WLL ton	For chain, 1-leg mm	For chain, 2-leg mm	A mm	B mm	D mm	Weight kg
NOR76	1.6	6/7	6	110	60	13	0.34
NOR87	2.12	8	7	110	60	16	0.53
NOR108	3.15	10	8	135	75	18	0.8
NOR1310	5.3	13	10	160	90	22	1.5
NOR1613	8	16	13	180	100	26	2.3
NOR1816	11.2	18	16	200	110	32	3.9
NOR2218	14	20	18	260	140	36	6.35
NOR2220	17	22	20	300	160	40	9
NOR2622	21.2	26	22	340	180	45	12.8
NOR3226	31.5	32	26	350	190	50	17.2
NOR3632	45	36	32	400	200	56	24.2