Master link, grade 80

Product information



Masterlink for chain sling assemblies.

... *Read more*

Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, yellow
Standard: EN 1677-4
Warning: Not to be heat-treated


Safety factor: 4:1
Grade: 8

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Master link, grade 80

Blueprint



Technical data / Spare Parts

Part code	WLL ton	For chain, 1-leg mm	For chain, 2-leg mm	A mm	B mm	D mm	Weight kg
NOR76	1.6	6/7	6	110	60	13	0.34
NOR87	2.12	8	7	110	60	16	0.53
NOR108	3.15	10	8	135	75	18	0.8
NOR1310	5.3	13	10	160	90	22	1.5
NOR1613	8	16	13	180	100	26	2.3
NOR1816	11.2	18	16	200	110	32	3.9
NOR2218	14	20	18	260	140	36	6.35
NOR2220	17	22	20	300	160	40	9
NOR2622	21.2	26	22	340	180	45	12.8
NOR3226	31.5	32	26	350	190	50	17.2
NOR3632	45	36	32	400	200	56	24.2

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved