

Shortening clutches, grade 100

Product information



Eye grab hook is used for shortening chain legs of a sling. The grab hook is attached to the master link with the same connection link as the chain.

... [Read more](#)

Material: Steel

Marking: CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, blue


Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

Shortening clutches, grade 100

Blueprint



Technical data / Spare Parts

| Part code | WLL ton | For chain Ø mm | A mm | B mm | C mm | D mm | M mm | N mm | Ø mm mm | L mm | Weight kg |
|------------|---------|----------------|------|------|------|------|------|------|---------|------|-----------|
| LYKATK1006 | 1.4 | 6 | 38 | 7.5 | 27 | 7.5 | 29 | 16 | 7.7 | 73 | 0.25 |
| LYKATK1078 | 2.5 | 8 | 50 | 9.5 | 33 | 9.5 | 36 | 23 | 9.5 | 92 | 0.41 |
| LYKATK1010 | 4 | 10 | 60 | 11.5 | 43 | 11.5 | 45.5 | 26 | 13.3 | 115 | 0.75 |
| LYKATK1013 | 6.7 | 13 | 79 | 15 | 55 | 15 | 54 | 34 | 16.3 | 149 | 1.67 |
| LYKATK1016 | 10 | 16 | 98 | 19 | 70 | 19 | 70 | 40 | 19.7 | 184 | 4.2 |