



Pipe Lifting Clamp TPH

Product information

General: Horizontal pipe lifting clamp TPH/TPH-HD - Non marking. Clamp for horizontal lifting and transporting of steel and concrete pipes without damaging the product.

Model THP: Standard clamp

Model THP-HD: special for extreme heavy duty lifting situations

Features:

- TPH Jaw is covered with a special high quality pressure resistant plastic.
- TPH-HD Jaw is covered with special high quality extreme high pressure resistant plastic.
- Maintenance-friendly clamps, plastic pressure resistant cover is easy to change.
- TPH-HD has special handle for easy handling.
- Compact design and high lifting capacity.
- Lightweight design for easy handling.
- Tough quality heavy duty body.

Marking: According to standard, Type, serial number, WLL, Jaw opening and CE marking.

Temperature range: TPH: - 40°C to + 50°C. / TPH-HD - 30°C to + 80°C.

Standard: EN 13155

Part code	Code	WLL ton	Jaw width mm	V mm	S mm	W mm	U mm	T mm	X mm	Y mm	Weight kg	Delivery time days
PTTPH151	1.5 TPH	1.5	40	120	70	50	185	16	41	25	2	14
PTTPH30	3 TPH	3	40	120	70	50	185	16	41	25	2	14
PTTPH40	4 TPH	4	50	140	70	58	204	26	41	25	3	14
PTTPH60	6 TPH	6	50	140	70	58	204	26	41	25	3	14
PTTPH80	8 TPH	8	70	140	70	58	224	26	45	25	3.4	14
PTTPH100	10TPH	10	70	140	70	58	224	26	85	45	5	14

Blueprint

