



Vertical Lifting Clamp TNMK

Product information

Vertical lifting clamp TNMK/STNMK/TNMK-A - Non marking. Clamp for vertical lifting and transporting of all plates and structures without marking, scratching and or damaging the material surface. Perfect for lifting materials such as (stainless) steel, aluminum, nature stone, composite, painted materials, wood, glass, plastic, etc.

Model TNMK: Standard clamp

Model STNMK: Clamp with enlarged jaw opening.

Model TNMK-A: with adjustable extra large jaw opening: 0 to 180 mm (A) (adjustable steps of 20 mm)

Features:

- With 2 special synthetic anti-friction pads to guarantee non-marking
- · Supplied with chain lifting shackle for flexible lifting
- Always equipped with a safety mechanism, ensuring the clamp does not slip when non-marking lifting force is applied and when load is being lowered
- Clamp is locked in closed as well as open position
- Lightweight, maintenance-friendly, heavy duty body
- No minimal WLL needed.

Marking: According to standard, CE-marked, Type, serial number, WLL, Jaw opening.

Temperature range: -10°C up to +60°C

Standard: EN 13155

Part code	Code	WLL ton	Jaw width mm	H mm	S mm	T mm	U mm	V mm	W mm	X mm	Y mm	Weight kg	Delivery time days
LTNMK05	0.5 TNMK	0.5	0-20	205	102	40	462	224	48	80	14	6	1
LTNMKE05	0.5 STNMK	0.5	17-37	205	102	40	462	241	48	80	14	6	14
LTNMK1	1 TNMK	1	0-30	232	105	40	470	282	46	80	14	6.5	14
LTNMK15	1.5 TNMK	1.5	0-40	232	105	40	470	282	46	80	14	6.5	14
LTNMK2	2 TNMK	2	0-50	362	124	50	704	408	63	80	18	15	14
LTNMK3	3 TNMK	3	0-60	362	124	50	704	408	63	80	18	15.5	14

Blueprint

