Concrete pipe lifting sling

Product information



Six different concrete pipe lifting sling with 2- and 3-legs. P model slings are equipped with a standard jaw. In the I model slings, the jaw is wider than normal, and in the K model slings, the jaw is higher than normal and is suitable for concrete pipes equipped with rubber rings. In all models, the chain length is 1.5 m.

Models:

- **KRT2P**: 2-legs | chain leg 1,5 m | standard jaw P-model
- **KRT2I**: 2-legs | chain leg 1,5 m | wide jaw I-model
- **KRT2K**: 2-legs | chain leg 1,5 m | high jaw K-model | with a rubber sealing pipe clamps
- **KRT3P**: 3-legs | chain leg 1,5 m | standard jaw P-model
- **KRT3I**: 3-legs | chain leg 1,5 m | wide jaw I-model
- **KRT3K**: 3-legs | chain leg 1,5 m | high jaw K-model | with a rubber sealing pipe clamps

You can also order the jaws individually – you can find them here.

... *Read more*

Material: Steel
Marking: CE-mark
Finish: Painted, yellow
Note: L-dimension is height of jaw's grip area
Warning: Not to be heat-treated

Safety factor: 4:1

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Concrete pipe lifting sling

Blueprint



Technical data / Spare Parts

Part code	Code	WLL ton	Jaw width mm	L mm	Weight kg
KRT2I	KRT2I	2	80-170	235	35
KRT2K	KRT2K	2	60-120	345	35
KRT2P	KRT2P	2	60-120	245	25
KRT3I	KRT3I	3	80-170	235	46
KRT3K	KRT3K	3	60-120	345	45
KRT3P	KRT3P	3	60-120	245	37

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved