Wire rope / cable pulling socks

Product information

For pulling steel wire ropes and cables.

Recommended safety factors:

- 3:1 for ground level horizontal drift
- 5:1 for overhead pull
- for high risk assessment applications 10:1

... *Read more*



Material: Steel
Finish: Hot dip galvanized
Warning: Not to be heat-treated

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Wire rope / cable pulling socks


Technical data / Spare Parts

Part code	Rope Ø range mm	MBL ton	Weight kg
VESUK1020	10-20	1.5	0.13
VESUK2030	20-30	2	0.2
VESUK3040	30-40	3.5	0.3
VESUK4050	40-50	5	0.5
VESUK5065	50-65	6	0.6
VESUK6580	65-80	8	1.05
VESUK8095	80-95	9	2.3

LENGTH OF SOCKS

Part code	Sock length (mm)	Total length (mm)
VESUK2030	600	680
VESUK3040	650	740
VESUK4050	700	820
VESUK5065	750	880
VESUK6580	850	1030
VESUK8095	950	1150

2-3% tolerance



Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved