



## Round slings assemblies 4-legs

### Product information

Lighter alternative to a chain combination in, for example, transformer lifting without risk of insulator damage etc. Also available with self-locking hooks, rotating swivel hooks, shackles etc.

**Features:** RFID-ready

**Material:** 100% polyester

**Marking:** CE-marked

**Temperature range:** -40°C - +100 °C

**Safety factor:** 4:1

Part code	WLL ton	WLL 0-45° t	WLL 45-60° t	Length m	Delivery time days
PRK1401	2.1	2.1	1.5	1	5
PRK1401.5	2.1	2.1	1.5	1.5	5
PRK1402	2.1	2.1	1.5	2	5
PRK1402.5	2.1	2.1	1.5	2.5	5
PRK1403	2.1	2.1	1.5	3	5
PRK1404	2.1	2.1	1.5	4	5

PRK2401	4.2	4.2	3,0	1	5
PRK2401.5	4.2	4.2	3,0	1.5	5
PRK2402	4.2	4.2	3,0	2	5
PRK2402.5	4.2	4.2	3,0	2.5	5
PRK2403	4.2	4.2	3,0	3	5
PRK2404	4.2	4.2	3,0	4	5
PRK3401	6.3	6.3	4,5	1	5
PRK3401.5	6.3	6.3	4,5	1.5	5
PRK3402	6.3	6.3	4,5	2	5
PRK3402.5	6.3	6.3	4,5	2.5	5
PRK3403	6.3	6.3	4,5	3	5
PRK3404	6.3	6.3	4,5	4	5
PRK5401	10.5	10.5	7,5	1	5
PRK5401.5	10.5	10.5	7,5	1.5	5
PRK5402	10.5	10.5	7,5	2	5
PRK5402.5	10.5	10.5	7,5	2.5	5
PRK5403	10.5	10.5	7,5	3	5
PRK5404	10.5	10.5	7,5	4	5
PRK8402	17	17	11,8	2	5
PRK8402.5	17	17	11,8	2.5	5
PRK8403	17	17	11,8	3	5
PRK8404	17	17	11,8	4	5
PRK8405	17	17	11,8	5	5

PRK8406

17

17

11,8

6

5