



Round slings assemblies 2-legs

Product information

Lighter alternative to a chain combination in, for example, transformer lifting without risk of insulator damage etc. Also available with self-locking hooks, rotating swivel hooks, shackles etc.

Features: RFID-ready

Material: 100% polyester

Marking: CE-marked

Temperature range: -40°C - +100 °C

Safety factor: 4:1

Part code	WLL ton	WLL 0-45° t	WLL 45-60° t	Length	Delivery time days
PRK1201	1.4	1.4	1,0	1	5
PRK1201.5	1.4	1.4	1,0	1.5	5
PRK1202	1.4	1.4	1,0	2	5
PRK1202.5	1.4	1.4	1,0	2.5	5
PRK1203	1.4	1.4	1,0	3	5
PRK1204	1.4	1.4	1,0	4	5

PRK2201	2.8	2.8	2,0	1	5
PRK2201.5	2.8	2.8	2,0	1.5	5
PRK2202	2.8	2.8	2,0	2	5
PRK2202.5	2.8	2.8	2,0	2.5	5
PRK2203	2.8	2.8	2,0	3	5
PRK2204	2.8	2.8	2,0	4	5
PRK3201	4.2	4.2	3,0	1	5
PRK3201.5	4.2	4.2	3,0	1.5	5
PRK3202	4.2	4.2	3,0	2	5
PRK3202.5	4.2	4.2	3,0	2.5	5
PRK3203	4.2	4.2	3,0	3	5
PRK3204	4.2	4.2	3,0	4	5
PRK5201	7	7	5,0	1	5
PRK5201.5	7	7	5,0	1.5	5
PRK5202	7	7	5,0	2	5
PRK5202.5	7	7	5,0	2.5	5
PRK5203	7	7	5,0	3	5
PRK5204	7	7	5,0	4	5
PRK8202	11.2	11.2	8,0	2	5
PRK8202.5	11.2	11.2	8,0	2.5	5
PRK8203	11.2	11.2	8,0	3	5
PRK8204	11.2	11.2	8,0	4	5
PRK8205	11.2	11.2	8,0	5	5

PRK8206	11.2	11.2	8,0	6	5
---------	------	------	-----	---	---