# Webbing slings 0,5 - 35 t

## Product information



Double layer Duplex webbing slings 0,5 - 35 t. Folded reinforced eyes as standard and also available with flat eye.

Note! Standard dimensional tolerance is ± 3%. Lengths can vary within the tolerance range!

Thanks to our own production unit, we can also make quick deliveries of special types and lengths as well as lifting slings with higher WLL UP TO 35t.

... *Read more*

**Features:** RFID-ready
**Material:** 100% polyester
**Marking:** According to standard, CE-mark
**Temperature range:** -40°C - +100 °C
**Standard:** EN 1492-1
**Note:** Color coded

**Safety factor:** 7:1

**Haklift Oy**
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

# Webbing slings 0,5 - 35 t

**Technical data / Spare Parts**

| Part code | WLL ton | Choke Hitch ton | Basket Hitch 0° ton | Basket Hitch 0-45° ton | Basket Hitch 45°-60° ton | EWL m | Webbing width mm | Packing | Colour |
|---|---|---|---|---|---|---|---|---|---|
| SNV0501 | 0.5 | 0.4 | 1 | 0.7 | 0.5 | 1 | 25 | 100 | White |
| SNV0502 | 0.5 | 0.4 | 1 | 0.7 | 0.5 | 2 | 25 | 50 | White |
| SNV0503 | 0.5 | 0.4 | 1 | 0.7 | 0.5 | 3 | 25 | 40 | White |
| SNV0504 | 0.5 | 0.4 | 1 | 0.7 | 0.5 | 4 | 25 | 35 | White |
| SNV0505 | 0.5 | 0.4 | 1 | 0.7 | 0.5 | 5 | 25 | 25 | White |
| SNV0506 | 0.5 | 0.4 | 1 | 0.7 | 0.5 | 6 | 25 | - | White |
| SNV0508 | 0.5 | 0.4 | 1 | 0.7 | 0.5 | 8 | 25 | - | White |
| SNV0510 | 0.5 | 0.4 | 1 | 0.7 | 0.5 | 10 | 25 | - | White |
| SNV05XX | 0.5 | 0.4 | 1 | 0.7 | 0.5 | - | 25 | - | White |
| SNV101 | 1 | 0.8 | 2 | 1.4 | 1 | 1 | 50 | 40 | Violet |
| SNV102 | 1 | 0.8 | 2 | 1.4 | 1 | 2 | 50 | 30 | Violet |
| SNV103 | 1 | 0.8 | 2 | 1.4 | 1 | 3 | 50 | 24 | Violet |
| SNV104 | 1 | 0.8 | 2 | 1.4 | 1 | 4 | 50 | 20 | Violet |
| SNV105 | 1 | 0.8 | 2 | 1.4 | 1 | 5 | 50 | 18 | Violet |
| SNV106 | 1 | 0.8 | 2 | 1.4 | 1 | 6 | 50 | 15 | Violet |
| SNV108 | 1 | 0.8 | 2 | 1.4 | 1 | 8 | 50 | 15 | Violet |
| SNV110 | 1 | 0.8 | 2 | 1.4 | 1 | 10 | 50 | 10 | Violet |
| SNV1XX | 1 | 0.8 | 2 | 1.4 | 1 | - | 50 | - | Violet |
| SNV201 | 2 | 1.6 | 4 | 2.8 | 2 | 1 | 60 | 50 | Green |
| SNV202 | 2 | 1.6 | 4 | 2.8 | 2 | 2 | 60 | 30 | Green |
| SNV203 | 2 | 1.6 | 4 | 2.8 | 2 | 3 | 60 | 25 | Green |
| SNV204 | 2 | 1.6 | 4 | 2.8 | 2 | 4 | 60 | 20 | Green |
| SNV205 | 2 | 1.6 | 4 | 2.8 | 2 | 5 | 60 | 15 | Green |
| SNV206 | 2 | 1.6 | 4 | 2.8 | 2 | 6 | 60 | 15 | Green |
| SNV208 | 2 | 1.6 | 4 | 2.8 | 2 | 8 | 60 | 12 | Green |
| SNV210 | 2 | 1.6 | 4 | 2.8 | 2 | 10 | 60 | 10 | Green |
| SNV2XX | 2 | 1.6 | 4 | 2.8 | 2 | - | 60 | - | Green |
| SNV301 | 3 | 2.4 | 6 | 4.2 | 3 | 1 | 90 | 35 | Yellow |
| SNV302 | 3 | 2.4 | 6 | 4.2 | 3 | 2 | 90 | 18 | Yellow |
| SNV303 | 3 | 2.4 | 6 | 4.2 | 3 | 3 | 90 | 15 | Yellow |

**Haklift Oy**
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

# Webbing slings 0,5 - 35 t

**Technical data / Spare Parts**

| Part code | WLL ton | Choke Hitch ton | Basket Hitch 0° ton | Basket Hitch 0-45° ton | Basket Hitch 45°-60° ton | EWL m | Webbing width mm | Packing | Colour |
|---|---|---|---|---|---|---|---|---|---|
| SNV304 | 3 | 2.4 | 6 | 4.2 | 3 | 4 | 90 | 12 | Yellow |
| SNV305 | 3 | 2.4 | 6 | 4.2 | 3 | 5 | 90 | 9 | Yellow |
| SNV306 | 3 | 2.4 | 6 | 4.2 | 3 | 6 | 90 | 9 | Yellow |
| SNV308 | 3 | 2.4 | 6 | 4.2 | 3 | 8 | 90 | 6 | Yellow |
| SNV310 | 3 | 2.4 | 6 | 4.2 | 3 | 10 | 90 | 6 | Yellow |
| SNV3XX | 3 | 2.4 | 6 | 4.2 | 3 | - | 90 | - | Yellow |
| SNV401 | 4 | 3.2 | 8 | 5.6 | 4 | 1 | 120 | 12 | Grey |
| SNV402 | 4 | 3.2 | 8 | 5.6 | 4 | 2 | 120 | 12 | Grey |
| SNV403 | 4 | 3.2 | 8 | 5.6 | 4 | 3 | 120 | 10 | Grey |
| SNV404 | 4 | 3.2 | 8 | 5.6 | 4 | 4 | 120 | 8 | Grey |
| SNV405 | 4 | 3.2 | 8 | 5.6 | 4 | 5 | 120 | 6 | Grey |
| SNV406 | 4 | 3.2 | 8 | 5.6 | 4 | 6 | 120 | 6 | Grey |
| SNV408 | 4 | 3.2 | 8 | 5.6 | 4 | 8 | 120 | 4 | Grey |
| SNV410 | 4 | 3.2 | 8 | 5.6 | 4 | 10 | 120 | 3 | Grey |
| SNV4XX | 4 | 3.2 | 8 | 5.6 | 4 | - | 120 | - | Grey |
| SNV502 | 5 | 4 | 10 | 7 | 5 | 2 | 150 | 10 | Red |
| SNV503 | 5 | 4 | 10 | 7 | 5 | 3 | 150 | 8 | Red |
| SNV504 | 5 | 4 | 10 | 7 | 5 | 4 | 150 | 6 | Red |
| SNV505 | 5 | 4 | 10 | 7 | 5 | 5 | 150 | 6 | Red |
| SNV506 | 5 | 4 | 10 | 7 | 5 | 6 | 150 | 4 | Red |
| SNV508 | 5 | 4 | 10 | 7 | 5 | 8 | 150 | 4 | Red |
| SNV510 | 5 | 4 | 10 | 7 | 5 | 10 | 150 | 4 | Red |
| SNV5XX | 5 | 4 | 10 | 7 | 5 | - | 150 | - | Red |
| SNV602 | 6 | 4.8 | 12 | 8.4 | 6 | 2 | 180 | 8 | Brown |
| SNV603 | 6 | 4.8 | 12 | 8.4 | 6 | 3 | 180 | 6 | Brown |
| SNV604 | 6 | 4.8 | 12 | 8.4 | 6 | 4 | 180 | 4 | Brown |
| SNV605 | 6 | 4.8 | 12 | 8.4 | 6 | 5 | 180 | 4 | Brown |
| SNV606 | 6 | 4.8 | 12 | 8.4 | 6 | 6 | 180 | 3 | Brown |
| SNV608 | 6 | 4.8 | 12 | 8.4 | 6 | 8 | 180 | 3 | Brown |
| SNV610 | 6 | 4.8 | 12 | 8.4 | 6 | 10 | 180 | 2 | Brown |

**Haklift Oy**
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

# Webbing slings 0,5 - 35 t

**Technical data / Spare Parts**

| Part code | WLL ton | Choke Hitch ton | Basket Hitch 0° ton | Basket Hitch 0-45° ton | Basket Hitch 45°-60° ton | EWL m | Webbing width mm | Packing | Colour |
|---|---|---|---|---|---|---|---|---|---|
| SNV6XX | 6 | 4.8 | 12 | 8.4 | 6 | - | 180 | - | Brown |
| SNV802 | 8 | 6.4 | 16 | 11.2 | 8 | 2 | 240 | 4 | Blue |
| SNV803 | 8 | 6.4 | 16 | 11.2 | 8 | 3 | 240 | 4 | Blue |
| SNV804 | 8 | 6.4 | 16 | 11.2 | 8 | 4 | 240 | 3 | Blue |
| SNV805 | 8 | 6.4 | 16 | 11.2 | 8 | 5 | 240 | 3 | Blue |
| SNV806 | 8 | 6.4 | 16 | 11.2 | 8 | 6 | 240 | 2 | Blue |
| SNV808 | 8 | 6.4 | 16 | 11.2 | 8 | 8 | 240 | 2 | Blue |
| SNV810 | 8 | 6.4 | 16 | 11.2 | 8 | 10 | 240 | 2 | Blue |
| SNV8XX | 8 | 6.4 | 16 | 11.2 | 8 | - | 240 | - | Blue |
| SNV820 | 8 | 6.4 | 16 | 11.2 | 8 | 20 | 240 | - | Blue |
| SNV1002 | 10 | 8 | 20 | 14 | 10 | 2 | 300 | - | Orange |
| SNV1003 | 10 | 8 | 20 | 14 | 10 | 3 | 300 | 3 | Orange |
| SNV1004 | 10 | 8 | 20 | 14 | 10 | 4 | 300 | 3 | Orange |
| SNV1005 | 10 | 8 | 20 | 14 | 10 | 5 | 300 | 2 | Orange |
| SNV1006 | 10 | 8 | 20 | 14 | 10 | 6 | 300 | 2 | Orange |
| SNV1008 | 10 | 8 | 20 | 14 | 10 | 8 | 300 | 2 | Orange |
| SNV1010 | 10 | 8 | 20 | 14 | 10 | 10 | 300 | 2 | Orange |
| SNV10XX | 10 | 8 | 20 | 14 | 10 | - | 300 | - | Orange |
| SNV1020 | 10 | 8 | 20 | 12 | 10 | 20 | 300 | - | Orange |
| SNV1204 | 12 | 9.6 | 24 | 16.8 | 12 | 4 | 300 | - | Orange |
| SNV1205 | 12 | 9.6 | 24 | 16.8 | 12 | 5 | 300 | - | Orange |
| SNV1206 | 12 | 9.6 | 24 | 16.8 | 12 | 6 | 300 | - | Orange |
| SNV1208 | 12 | 9.6 | 24 | 16.8 | 12 | 8 | 300 | - | Orange |
| SNV1210 | 12 | 9.6 | 24 | 16.8 | 12 | 10 | 300 | - | Orange |
| SNV12XX | 12 | 9.6 | 24 | 16.8 | 12 | - | 300 | - | Orange |
| SNV1220 | 12 | 9.6 | 24 | 16.8 | 12 | 20 | 300 | - | Orange |

**Haklift Oy**
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved