

Webbing slings 0,5 - 35 t

Product information



Double layer Duplex webbing slings 0,5 - 35 t. Folded reinforced eyes as standard and also available with flat eye.

Note! Standard dimensional tolerance is $\pm 3\%$. Lengths can vary within the tolerance range!

Thanks to our own production unit, we can also make quick deliveries of special types and lengths as well as lifting slings with higher WLL UP TO 35t.

[... Read more](#)

Features: RFID-ready

Material: 100% polyester

Marking: According to standard, CE-marked

Temperature range: -40°C - +100 °C

Standard: EN 1492-1

Note: Color coded

Safety factor: 7:1

Webbing slings 0,5 - 35 t

Technical data / Spare Parts

Part code	WLL ton	Choke Hitch ton	Basket Hitch 0° ton	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	EWL m	Webbing width mm	Packing	Colour
SNV0501	0.5	0.4	1	0.7	0.5	1	25	100	White
SNV0502	0.5	0.4	1	0.7	0.5	2	25	50	White
SNV0503	0.5	0.4	1	0.7	0.5	3	25	40	White
SNV0504	0.5	0.4	1	0.7	0.5	4	25	35	White
SNV0505	0.5	0.4	1	0.7	0.5	5	25	25	White
SNV0506	0.5	0.4	1	0.7	0.5	6	25	-	White
SNV0508	0.5	0.4	1	0.7	0.5	8	25	-	White
SNV0510	0.5	0.4	1	0.7	0.5	10	25	-	White
SNV05XX	0.5	0.4	1	0.7	0.5	-	25	-	White
SNV101	1	0.8	2	1.4	1	1	50	40	Violet
SNV102	1	0.8	2	1.4	1	2	50	30	Violet
SNV103	1	0.8	2	1.4	1	3	50	24	Violet
SNV104	1	0.8	2	1.4	1	4	50	20	Violet
SNV105	1	0.8	2	1.4	1	5	50	18	Violet
SNV106	1	0.8	2	1.4	1	6	50	15	Violet
SNV108	1	0.8	2	1.4	1	8	50	15	Violet
SNV110	1	0.8	2	1.4	1	10	50	10	Violet
SNV1XX	1	0.8	2	1.4	1	-	50	-	Violet
SNV201	2	1.6	4	2.8	2	1	60	50	Green
SNV202	2	1.6	4	2.8	2	2	60	30	Green
SNV203	2	1.6	4	2.8	2	3	60	25	Green
SNV204	2	1.6	4	2.8	2	4	60	20	Green
SNV205	2	1.6	4	2.8	2	5	60	15	Green
SNV206	2	1.6	4	2.8	2	6	60	15	Green
SNV208	2	1.6	4	2.8	2	8	60	12	Green
SNV210	2	1.6	4	2.8	2	10	60	10	Green
SNV2XX	2	1.6	4	2.8	2	-	60	-	Green
SNV301	3	2.4	6	4.2	3	1	90	35	Yellow
SNV302	3	2.4	6	4.2	3	2	90	18	Yellow
SNV303	3	2.4	6	4.2	3	3	90	15	Yellow

Webbing slings 0,5 - 35 t

Technical data / Spare Parts

Part code	WLL ton	Choke Hitch ton	Basket Hitch 0° ton	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	EWL m	Webbing width mm	Packing	Colour
SNV304	3	2.4	6	4.2	3	4	90	12	Yellow
SNV305	3	2.4	6	4.2	3	5	90	9	Yellow
SNV306	3	2.4	6	4.2	3	6	90	9	Yellow
SNV308	3	2.4	6	4.2	3	8	90	6	Yellow
SNV310	3	2.4	6	4.2	3	10	90	6	Yellow
SNV3XX	3	2.4	6	4.2	3	-	90	-	Yellow
SNV401	4	3.2	8	5.6	4	1	120	12	Grey
SNV402	4	3.2	8	5.6	4	2	120	12	Grey
SNV403	4	3.2	8	5.6	4	3	120	10	Grey
SNV404	4	3.2	8	5.6	4	4	120	8	Grey
SNV405	4	3.2	8	5.6	4	5	120	6	Grey
SNV406	4	3.2	8	5.6	4	6	120	6	Grey
SNV408	4	3.2	8	5.6	4	8	120	4	Grey
SNV410	4	3.2	8	5.6	4	10	120	3	Grey
SNV4XX	4	3.2	8	5.6	4	-	120	-	Grey
SNV502	5	4	10	7	5	2	150	10	Red
SNV503	5	4	10	7	5	3	150	8	Red
SNV504	5	4	10	7	5	4	150	6	Red
SNV505	5	4	10	7	5	5	150	6	Red
SNV506	5	4	10	7	5	6	150	4	Red
SNV508	5	4	10	7	5	8	150	4	Red
SNV510	5	4	10	7	5	10	150	4	Red
SNV5XX	5	4	10	7	5	-	150	-	Red
SNV602	6	4.8	12	8.4	6	2	180	8	Brown
SNV603	6	4.8	12	8.4	6	3	180	6	Brown
SNV604	6	4.8	12	8.4	6	4	180	4	Brown
SNV605	6	4.8	12	8.4	6	5	180	4	Brown
SNV606	6	4.8	12	8.4	6	6	180	3	Brown
SNV608	6	4.8	12	8.4	6	8	180	3	Brown
SNV610	6	4.8	12	8.4	6	10	180	2	Brown

Webbing slings 0,5 - 35 t

Technical data / Spare Parts

Part code	WLL ton	Choke Hitch ton	Basket Hitch 0° ton	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	EWL m	Webbing width mm	Packing	Colour
SNV6XX	6	4.8	12	8.4	6	-	180	-	Brown
SNV802	8	6.4	16	11.2	8	2	240	4	Blue
SNV803	8	6.4	16	11.2	8	3	240	4	Blue
SNV804	8	6.4	16	11.2	8	4	240	3	Blue
SNV805	8	6.4	16	11.2	8	5	240	3	Blue
SNV806	8	6.4	16	11.2	8	6	240	2	Blue
SNV808	8	6.4	16	11.2	8	8	240	2	Blue
SNV810	8	6.4	16	11.2	8	10	240	2	Blue
SNV8XX	8	6.4	16	11.2	8	-	240	-	Blue
SNV820	8	6.4	16	11.2	8	20	240	-	Blue
SNV1002	10	8	20	14	10	2	300	-	Orange
SNV1003	10	8	20	14	10	3	300	3	Orange
SNV1004	10	8	20	14	10	4	300	3	Orange
SNV1005	10	8	20	14	10	5	300	2	Orange
SNV1006	10	8	20	14	10	6	300	2	Orange
SNV1008	10	8	20	14	10	8	300	2	Orange
SNV1010	10	8	20	14	10	10	300	2	Orange
SNV10XX	10	8	20	14	10	-	300	-	Orange
SNV1020	10	8	20	12	10	20	300	-	Orange
SNV1204	12	9.6	24	16.8	12	4	300	-	Orange
SNV1205	12	9.6	24	16.8	12	5	300	-	Orange
SNV1206	12	9.6	24	16.8	12	6	300	-	Orange
SNV1208	12	9.6	24	16.8	12	8	300	-	Orange
SNV1210	12	9.6	24	16.8	12	10	300	-	Orange
SNV12XX	12	9.6	24	16.8	12	-	300	-	Orange
SNV1220	12	9.6	24	16.8	12	20	300	-	Orange