



Double Swivel Ring Codipro SS DSR

Product information



Stainless Steel Double Swivel Ring: SS DSR.

Double articulation allows it to line up perfectly with the sling.

From M8 to M30 as standard; for loads from 0.3 t to 3 t.

Features:

- Rotatable under load.
- Two ways of tightening:- Allen key or Torque wrench(also for external hex)

Material: AISI 316 L

Marking: According to standard, CE-marked

Temperature range: -20°C up to + 200°C

Standard: EN 1677-1

except grade/WLL

Safety factor: 5:1

Part Code	WLL ton	Thread	Torque Nm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	L1 mm	S1 mm	S2 mm	Weight kg
NS8KL06SS.DSR	0.1	M 6 (x1)	4	32	30	30	39	28	13	53	9.5	15	8	16	0.3
NS8KL08SS.DSR	0.3	M 8 (x1.25)	6	32	30	30	39	28	13	53	9.5	16	8	16	0.3
NS8KL10SS.DSR	0.5	M 10 (x1.50)	10	32	30	30	39	28	13	53	9.5	16	8	16	0.3
NS8KL12SS.DSR	0.8	M 12 (x1.75)	15	32	30	30	39	28	13	53	9.5	19	8	16	0.3
NS8KL14SS.DSR	1	M 14 (x2)	30	44	40	45	53	38	17	76	13	29	8	20	0.9
NS8KL16SS.DSR	1.4	M 16 (x2)	50	44	40	45	53	38	17	76	13	26	8	20	0.9
NS8KL18SS.DSR	1.4	M 18 (x2.5)	70	44	40	45	53	38	17	76	13	30	8	20	1
NS8KL20SS.DSR	1.4	M 20 (x2.5)	100	44	40	45	53	38	17	76	13	30	8	20	1
NS8KL22SS.DSR	2.2	M 22 (x2.5)	120	62	55	58	83	56	25	115	19	42	14	24	2.5
NS8KL24SS.DSR	2.7	M 24 (x3)	160	62	55	58	83	56	25	115	19	42	14	24	2.6
NS8KL27SS.DSR	2.8	M 27 (x3)	200	62	55	58	83	56	25	115	19	42	14	24	2.7
NS8KL30SS.DSR	3	M 30 (x3.5)	250	62	55	58	83	56	25	115	19	47	14	24	2.8

Blueprint

