Double Swivel Shackle Codipro SS DSS

Product information



The SS.DSS stainless steel lifting ring is a double swivel ring. It is specially designed for simultaneously lifting and rotating loads. Its double swivel action ensures perfect alignment with the sling.

Features:

- Stainless steel ring that provides maximum corrosion resistance.
- Rotatable under load.
- M45 to M56 or UNC thread available on request.

... *Read more*

Material: AISI 316 L
Marking: According to standard, CE-mark
Temperature range: -20°C up to + 200°C
Standard: EN 1677-1
except grade/WLL


Safety factor: 5:1

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Double Swivel Shackle Codipro SS DSS

Blueprint



Technical data / Spare Parts

Part code	WLL ton	Thread	Torque Nm	StandardL1 mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	L1 mm	S mm	Weight kg
NS8KL24SS.DSS	2.7	M 24 (x3)	160	36	61	31	70	98	73	149	30	36	19	5.2
NS8KL30SS.DSS	3.5	M 30 (x3.5)	250	45	61	31	70	98	73	149	30	45	19	5.2
NS8KL33SS.DSS	3.5	M 33 (x3.5)	250	50	61	31	70	98	73	149	30	50	19	5.2
NS8KL36SS.DSS	5	M 36 (x4)	320	54	61	31	70	98	73	149	30	54	19	5.2
NS8KL363SS.DSS	5	M 36 (x3)	320	54	61	31	70	98	73	149	30	54	19	5.2
NS8KL39SS.DSS	5	M 39 (x4)	320	54	61	31	70	98	73	149	30	54	19	5.4
NS8KL42SS.DSS	6	M 42 (x4,5)	400	63	61	31	70	98	73	149	30	63	19	5.4
NS8KL423SS.DSS	6	M 42 (x3)	400	63	61	31	70	98	73	149	30	63	19	5.4

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved