
Female Double Swivel Shackle Codipro SS FE DSS

Product information



Stainless steel female double swivel shackle SS FE DSS.

Design: Centered lifting ring with double articulation except for the SEB, swivel eyebolt 360°.

... *Read more*

Material: AISI 316 L
Marking: According to standard, CE-marked, The compliance to EC directives, GRADUP steel quality, The recommended tightening torque, The manufacturer brand, Tracebility marks of each component (Blacksmith + batch number), The thread
Temperature range: -20°C up to + 200°C
Finish: An anti-corrosion coating on the unpainted parts of the CODIPRO swivel lifting points and orange color (RAL 2002) for the schackle.
Standard: EN 1677-1
except grade/WLL


Safety factor: 5:1

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Female Double Swivel Shackle Codipro SS FE DSS

Blueprint



Technical data / Spare Parts

Part code	WLL ton	Thread	Torque Nm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	L max. mm	S mm	Weight kg
NS8KL24SS.FE.DSS	2.7	M 24 (x3)	160	66	31	70	98	73	149	30	66	50	5.8
NS8KL30SS.FE.DSS	3.5	M 30 (x3.5)	250	66	31	70	98	73	149	30	66	50	5.8
NS8KL33SS.FE.DSS	3.5	M 33 (x3.5)	250	66	31	70	98	73	149	30	66	50	5.8
NS8KL36SS.FE.DSS	5	M 36 (x4)	320	66	31	70	98	73	149	30	66	50	5.8

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved