Lifting Eye Super Point 8-251

Product information



Pivots to 230°, rotates through 360° due to its unique ball bearing design.
Certified by DGUV GS-OA-15-04.
Load rated parts are 100% magnaflux crack detected.
Individual forged parts and batch code links to Test Certificate sheet.
Bolt are Metric thread (ASME / ANSI B18.3.1M).
Proof tested to 2.5 times the WLL.
Fatigue rated to 1.5 times the WLL.
Easy to attach or dismantle due to the forged hexagon shaped body of the Super Point.

Capable of rotating under load.

With the new WLL tables you can find the right Super Point attachment for your application and by the red marking on both sides you can measure disposal stage of the Super Point.

... *Read more*

Features: Built-in RFID/NFC chip
Material: Forged alloy steel, quenched and tempered.
Marking: According to standard, CE-mark
Temperature range: -40°C - +200°C
Standard: EN 1677-1
Warning: Do not turn continuously in 90 degree direction at full load.


Safety factor: 4:1

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Lifting Eye Super Point 8-251

Blueprint



Technical data / Spare Parts

Part code	WLL ton	Thread mm	Torque Nm	Thread length mm	Pitch DIN13	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	K mm	M mm	Weight kg
NS10KL10005Y	0.5	M10	10-40	18	1.5	35	53	48	13	18	101	36.5	20.5	34	M10	0.4
NS10KL12007Y	0.7	M12	15-40	18	1.75	35	53	48	13	18	101	36.5	20.5	34	M12	0.4
NS10KL16014Y	1.4	M16	45-130	20	2	35	53	48	13	20	101	36.5	20.5	34	M16	0.44
NS10KL20025Y	2.5	M20	100-170	30	2.5	35	59	68	16	30	127	52	28	46	M20	1
NS10KL2404Y	4	M24	190-280	30	3	40	73	75	19	30	148	57	34.5	50	M24	1.5
NS10KL3067Y	6.7	M30	230-400	35	3.5	40	68	95	19	35	163	70	41	65	M30	2.4
NS10KL3610Y	10	M36	270-600	50	4	50	95	106	22	50	201	81	48	75	M36	3.8
NS10KL42125Y	12.5	M42	270-700	60	4.5	50	95	106	22	60	201	81	48	75	M42	4

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved