Double Swivel Ring Codipro DSR UP

Product information



The double swivel ring DSR UP has been especially designed to guarantee liftings under load. Its double articulation allows it to line up perfectly with the sling.

Features:

- Swiveling under load
- Usable for any kind of lifting operation
- Two ways of tightening:- Allen key or torque wrench (also for external hex)
- The tightening torque is stamped on all lifting rings in the GRADUP range

... *Read more*

Material: High tensile steel
Marking: According to standard, CE-mark
Temperature range: -20°C up to +200°C
Standard: EN 1677-1
except grade/WLL


Safety factor: 5:1

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Double Swivel Ring Codipro DSR UP

Blueprint



Technical data / Spare Parts

Part code	WLL ton	Thread mm	Torque Nm	Thread	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	L1 mm	S1 mm mm	S2 mm mm	Weight kg
NS8KL05M	0.07	M5 (x0.8)	3	-	33	30	30	38	27	14	53	9.5	15	8	16	0.3
NS8KL06M	0.15	-	4	M6 (x1)	33	30	30	38	27	14	53	9.5	15	8	16	0.3
NS8KL08M	0.4	-	6	M8 (x1.25)	33	30	30	38	27	14	53	9.5	15	8	16	0.3
NS8KL10M	0.7	-	10	M10 (x1.50)	33	30	30	38	27	14	53	9.5	18	8	16	0.3
NS8KL12M	1.05	-	15	M12 (x1.75)	33	30	30	38	27	14	53	9.5	21	8	16	0.3
NS8KL14M	1.4	-	30	M14 (x2)	45	40	45	53	38	17	76	13	23	8	20	0.9
NS8KL16M	2	-	50	M16 (x2)	45	40	45	53	38	17	76	13	27	8	20	0.9
NS8KL18M	2.3	-	70	M18 (x2.5)	45	40	45	53	38	17	76	13	27	8	20	0.9
NS8KL20M	2.5	-	100	M20 (x2.5)	45	40	45	53	38	17	76	13	30	8	20	0.9
NS8KL22M	3.5	-	120	M22 (x2.5)	62	55	60	83	55	25	115	19	33	14	24	2.6
NS8KL24M	4.4	-	160	M24 (x3)	62	55	60	83	55	25	115	19	36	14	24	2.6
NS8KL27M	5.7	-	200	M27 (x3)	62	55	60	83	55	25	115	19	40	14	24	2.7
NS8KL30M	6	-	250	M30 (x3.5)	62	55	60	83	55	25	115	19	45	14	24	2.7

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved