

## Stainless steel lifting eye nut DIN 582



### Product information

Stainless steel lifting eye for vertical lifting.

**Material:** AISI 316

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C - (+)200°C

**Finish:** Polished

**Standard:** DIN 582

**Note:** Only for vertical lifting

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

Part code	WLL ton	Thread mm	b mm	c mm	d mm	e mm	f mm	Weight kg	Delivery time days
NSMH06L	0.08	M6	20	36	20	8.5	36	0.05	1
NSMH08L	0.14	M8	20	36	20	8.5	36	0.05	1
NSMH10L	0.23	M10	25	45	25	10	45	0.09	1
NSMH12L	0.34	M12	30	54	30	11	53	0.16	1
NSMH16L	0.7	M16	35	63	35	13	62	0.24	1
NSMH20L	1.2	M20	39	71	39	14	70	0.36	1

## Technical data / Spare Parts

### WORKING LOAD LIMITS

Thread	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)
					0 - 45°	45-60°	0 - 45°	45-60°
M6	0,08		0,16		-		-	
M8	0,14		0,28		0,1		0,14	
M10	0,23		0,46					

## Blueprint

